

Extra-Duty IN BOX™ Replacement Covers

Replacement covers sold separately. Clear is not paintable and white is textured, paintable. UV rated plastic for long outdoor life.



DBVC




DBV2W

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	ORIENTATION/COVER COLOR	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
DBVC	77640	Single-Gang, Vert. / Clear	10	10	5.650	3.420	.370
DBVW	77642	Single-Gang, Vert. / White	10	10	5.650	3.420	.370
DBHC	77650	Single-Gang, Horiz. / Clear	10	10	3.420	5.650	.370
DBHW	77652	Single-Gang, Horiz. / White	10	10	3.420	5.650	.370
DBV2C	13009	2-Gang, Vert. / Clear	10	10	5.650	5.410	.370
DBV2W	13010	2-Gang, Vert. / White	10	10	5.650	5.410	.370

Note: Meets 2015 CEC (Rule 26-702), NEMA 3R, NEC 406.9 (b); Where a weatherproof-in-use cover is required for 15 or 20 AMP receptacles installed outdoors.

EXTRA-DUTY



Weatherproof Box Holder


Zinc die-cast and non-metallic.



CATALOG NUMBER	UPC/DCI/NAED MFG #018997	TRADE SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D
FS50	61050	1/2	25	25	.380	1.550	1.125	.860
FS75	61075	3/4	25	25	.380	1.550	1.125	.860
NMFS50*	54050	1/2	25	25	.380	1.550	1.125	.860
NMFS75	54075	3/4	25	25	.380	1.550	1.125	.860

*UV rated non-metallic body.

Note: Can be used as an external means of support to meet the requirements of 2014 NEC Section 314.23.



ASSEMBLY INSTRUCTIONS

Just screw the box support into the electrical box; the entire assembly is held secure with a 1/2" rigid steel conduit or water pipe.

Other Uses

- Stubbing up electrical enclosures above concrete slabs with rigid pipe.
- Suspending electrical boxes with rigid pipe between bar joists.
- Suspending fire alarms (smoke detectors) with rigid pipe between bar joists.
- Can be used for installation of equipment where a rigid pipe can be used for a holding means and a 1/2" knockout is present for attachment.

