

Low Voltage Mounting Brackets

Single through 4-gang brackets for installations on existing construction. Designed to install low voltage Class 2 only.

FEATURES AND BENEFITS


- Non-metallic—better than metal and costs less too!
- For communications, cable TV, computer wiring.
- Cat 5 listed
- Adjusts to fit 1/4" to 1" thick wallboard, paneling, or drywall
- Bracket is its own template for cut out
- Mounting wings hold bracket securely against wall when screws are tightened




LV1



LV2



LV3





LV4

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | DIM D | DIM E |
|----------------|--------------------------|----------|---------|-------|-------|-------|-------|-----------|
| LV1 | 58175 | 10 | 100 | 5.460 | 4.250 | 2.500 | 1.690 | 1/4" - 1" |
| LV2 | 10952 | 5 | 50 | 5.460 | 4.250 | 4.185 | 1.750 | 1/4" - 1" |
| LV3 | 09600 | 5 | 50 | 5.570 | 4.250 | 6.000 | 1.700 | 1/4" - 1" |
| LV4 | 09601 | 5 | 50 | 5.570 | 4.250 | 7.810 | 1.700 | 1/4" - 1" |

DIM E refers to wall thickness adjustment.
PATENTED.



Scan For Video




FINISHED INSTALLATION



Locate bracket position. Level. Trace inside of LV1 and cut on the outside of the line.

LOW VOLTAGE FIRE ALARM INSTALLATIONS



Arlington's LV2, for existing construction, and LVMB2, for new construction (see pg. O-4), can also be used for the installation of fire alarms.

Round Low Voltage Mounting Bracket



LVR1

Round mounting bracket for low voltage smoke detectors, carbon monoxide detectors, cameras & more—or any low voltage products that mount to a standard 4" fixture box.

FEATURES AND BENEFITS

- Mounting wing screws hold bracket secure
- Adjustable depth—fits 1/4" to 1-1/2" wall or ceiling thickness
- Fast, easy solution to mounting

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | DESCRIPTION | UNIT PKG | STD PKG | DIM A | DIM B |
|----------------|--------------------------|-------------|----------|---------|-------|-------|
| LVR1 | 58185 | 4" Round | 25 | 25 | 4.375 | 2.125 |