



LASSO

12V MINI PENDANTS

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with handcrafted glass.

LAMPING

Standard: 50W Low pressure halogen GY6.35 12V Bi-Pin lamp, lamp included. Suitable for use in an open fixture. Optional lamp shield also available.

LED: 6W integrated lightsource, dimmable. (Available on 1XT or 1XC fixtures only).

DIFFUSER

Shade shall be handcrafted glass of various decors. 4.75" Dia. x 3" H

Opening sizes: 24mm top.

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish. Cords also available in 15' lengths.

STANDARD PENDANT (1XC, 1XT)

Mini pendant comes complete with either dome-style or flat-style canopy.

QUICK-CONNECT OPTION (XP, RXP, 1XP)

Quick-Connect Jack is compatible with Besa Rail Adapter, or Quick-Connect canopies (order separately).

METAL FINISH


Glass retainer hardware, sleeve and Quick-Connect Jack and/or canopies are finished in either Bronze or Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



LASSO SHOWN IN GLITTER (5612GL) & GOLD GLITTER (5612GD)



561207
OPAL MATTE



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



LASSO

12V MINI PENDANTS

ORDERING:


CONNECTION	GLASS OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
Quick-Connect	561207 Opal Matte	(blank) 50W Hal	BR Bronze	L 15' cord
XP Jack Only	5612GD Gold Glitter	LED* 6W LED	SN Satin Nickel	
RXP Rail-Ready	5612GL Glitter	*LED option is for 1XC or 1XT fixtures ONLY. Consult factory for LED multilight options		
1XP Flat Canopy				
Pendant Fixtures				
1XC Dome Canopy				
1XT Flat Canopy				
Adjustable				
1XA Flat Canopy				

Ex. 1XT-5612GL-SN

Lasso Mini Pendant w/ Glitter Glass,
Satin Nickel Finish


QUICK-CONNECT OPTIONS:

XP Pendant Element Only



- Pendant Shade and Cord/Socket Set
- 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
- Quick-Connect Jack provided
- Compatible with Besa Canopies and Rail Adapter
- Bronze or Satin Nickel metal finishes


RXP Pendant + Rail Adapter



READY FOR RAIL

- Pendant Shade and Cord/Socket Set, plus Rail Adapter
- 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
- Quick-Connect Jack provided
- Compatible with Besa Monorail System
- Bronze or Satin Nickel metal finishes


1XP Pendant + Monopoint Flat Canopy



- Pendant Shade and Cord/Socket Set, plus Flat Canopy
- 1x electronic 60W dimmable transformer, fits partially in junction box
- 10' Field-adjustable braided coaxial-type cord with a teflon jacket (clear or bronze tint coordinates with metal finish)
- Quick-Connect Jack provided
- Integral Quick-Connect adapter
- Bronze or Satin Nickel metal finishes

FIXED PENDANT OPTIONS:


1XC 1 Light Pendant, Dome Canopy



NO CORD CUTTING REQUIRED

- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

MORE MOUNTING OPTIONS:

- Besa quick-connect canopies, order separately



- Besa Monorail system, order separately

LED 12V MINI PENDANTS:

- LED driver is located in canopy for optimal performance
- Total power of 6 watts
- 450 lumens
- Rated life: 30,000 hours
- CCT: 2800° Kelvin
- CRI: 85+
- Dimmable
- Frosted acrylic diffuser encloses LEDs

CORD LENGTH OPTIONS:

15Ft. CORD LENGTH:

For longer 15' cord, add an "L" to the end of the item number,
i.e. 1XP-174352-SNL.

Project Information:



LASSO

12V ADJUSTABLE PENDANTS

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Low-voltage adjustable mini pendant with handcrafted glass.
Up or down adjusting is achieved by squeezing the cable adjuster,
then releasing to lock in position.

LAMPING

50W Low pressure halogen GY6.35 12V Bi-Pin lamp, included. Suitable for use
in an open fixture.

DIFFUSER

Shade shall be handcrafted glass of various decors. 4.75" Dia. x 3"H
Opening sizes: 24mm top.

CABLE

Standard is 8' bare silver-color braided cable, length may be field-adjusted.

STANDARD PENDANT (1XA)

Adjustable pendant comes complete with quick-connect jack (includes
swivel/pivot feature) and a Quick-Connect canopy.

METAL FINISH

Glass retainer hardware, adjuster and Quick-connect are finished in either
Bronze or Satin Nickel.

LABELS

ETL or UL Listed. Suitable for Dry Locations (interior use only).



LASSO SHOWN IN GLITTER (5612GL) & OPAL MATTE (561207)



5612GD
GOLD GLITTER



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



BESA LIGHTING

LASSO

12V ADJUSTABLE PENDANTS

ORDERING:


CONNECTION	-	GLASS OPTIONS	-	LAMP OPTIONS	-	METAL FINISH
Adjustable		561207 Opal Matte		(blank) 50W Hal		BR Bronze
1XA Flat Canopy		5612GL Glitter				SN Satin Nickel
		5612GD Gold Glitter				

Ex. 1XA-5612GD-SN

Lasso Adjustable Pendant w/ Gold Glitter Glass,
Satin Nickel Finish

PENDANT OPTIONS:

1XA Adjustable Pendant + Monopoint Flat Canopy



- Easy cord adjuster, just squeeze and move up/down
- Pendant Shade and Cord/Socket Set, plus Flat Canopy
- 1x electronic 60W dimmable transformer, fits partially in junction box
- 8' Field-adjustable bare silver-color braided cable
- Swivel/pivot feature, suitable for use on sloped ceilings
- Quick-Connect Jack provided
- Integral Quick-Connect adapter
- Bronze or Satin Nickel metal finishes

Project Information: