

E-Z Lock™ Connectors - Zinc Plated Steel



AMC-50



AMC-5075



AMC-52

Used to connect AC/MC cable and flexible metal conduit to box or enclosure. Use slotted, Phillips or Robertson head screwdriver. Refer to the cable connector compatibility charts in the technical guide section for MCI-A and other cables. Use with anti-short bushing. Patented. US Patent D360,188.

cUL^{us} File No. E20534

Zinc Plated Steel / Insulated Throat - 105°C

| Catalog Number | K.O. Size | Flex Trade Size | AC/MC Cable Range | | Throat Opening | Unit Qty. | Std. Pkg. |
|----------------|-----------|-----------------|-------------------|-------------|----------------|-----------|-----------|
| | | | Min. | Max. | | | |
| AMC-50 | 1/2" | 3/8" | 14/2 (.40") | 10/3 (.62") | .406" | 50 | 500 |
| AMC-5075 | 1/2" | 1/2" | 10/4 (.62") | 6/4 (.92") | .565" | 25 | 250 |
| AMC-52 | 1/2" | 3/8" | 14/2 (.43") | 10/3 (.62") | .560" | 25 | 250 |
| AMC-75 | 3/4" | 3/4" | 10/3 (.56") | 6/3 (.81") | .560" | 25 | 100 |

Quick Install

E-Z Lock™ Connectors - Zinc Plated Steel



AMC-50QI



AMC-52QI

NEW

Used to connect AC/MC cable and flexible metal conduit to box or enclosure. No Tools Required! Just Squeeze to insert into the KO. Refer to the cable connector compatibility charts in the technical guide section for MCI-A and other cables. Use with anti-short bushing. Patented. US Patent 9,640,966.

cETL^{us} Listed

Zinc Plated Steel / Insulated Throat - 105°C

| Catalog Number | K.O. Size | Flex Trade Size | AC/MC Cable Range | | Throat Opening | Unit Qty. | Std. Pkg. |
|----------------|-----------|-----------------|-------------------|-------------|----------------|-----------|-----------|
| | | | Min. | Max. | | | |
| AMC-50QI | 1/2" | 3/8" | 14/2 (.40") | 10/3 (.62") | .406" | 50 | 500 |
| AMC-52QI | 1/2" | 3/8" | (2) 14/2 (.43") | 10/2 (.59") | .375" | 25 | 250 |

Quick Install

Flexible Metal Conduit Fittings

E-Z Lock™ Connectors - Zinc Plated Steel



AMC-50



AMC-5075



AMC-52

Used to connect flexible metal conduit to box or enclosure. Use slotted or Phillips head screwdriver. Also see AC/MC section for additional listings. Use with anti-short bushing. Patented. US Patent D360,188.

cUL_{us} File No. E20534

Zinc Plated Steel / Insulated Throat - 105°C

| Catalog Number | K.O. Size | Flex Trade Size | Throat Opening | Unit Qty. | Std. Pkg. |
|----------------|-----------|-----------------|----------------|-----------|-----------|
| AMC-50 | 1/2" | 3/8" | .406" | 50 | 500 |
| AMC-5075 | 1/2" | 1/2" | .565" | 25 | 250 |
| AMC-52 | 1/2" | 3/8" | .560" | 25 | 250 |
| AMC-75 | 3/4" | 3/4" | .560" | 25 | 100 |

Quick Install

E-Z Lock™ Connectors - Zinc Plated Steel



AMC-50QI



AMC-52QI

NEW

Used to connect AC/MC cable and flexible metal conduit to box or enclosure. No Tools Required! Just Squeeze to insert into the KO. Refer to the cable connector compatibility charts in the technical guide section for MCI-A and other cables. Use with anti-short bushing. Patented. US Patent 9,640,966.

cETL_{us} Listed

Zinc Plated Steel / Insulated Throat - 105°C

| Catalog Number | K.O. Size | Flex Trade Size | AC/MC Cable Range | | Throat Opening | Unit Qty. | Std. Pkg. |
|----------------|-----------|-----------------|-------------------|-------------|----------------|-----------|-----------|
| | | | Min. | Max. | | | |
| AMC-50QI | 1/2" | 3/8" | 14/2 (.40") | 10/3 (.62") | .406" | 50 | 500 |
| AMC-52QI | 1/2" | 3/8" | (2) 14/2 (.43") | 10/2 (.59") | .375" | 25 | 250 |


Quick Install

Armored/Metal Clad Cable Fittings

Fire Alarm Cable Color-Coded Connectors



Suitable for use with AC/MC and Fire Alarm MC Cable. Patented.
US Patent 6,817,895.

 File No. E20534

Zinc Die Cast / Insulated Throat - 105°C

| Catalog Number | | K.O. Color | Size | Fire Alarm | | AC/MC | | Unit Std. Qty. Pkg. | |
|-------------------|-----|---------------|-------------------|---------------------|---------------------|---------------------|---------------------|------------------------|--|
| | | | | Cable Range Min. | Cable Range Max. | Cable Range Min. | Cable Range Max. | | |
| 570-RI | Red | 1/2" | 18/2 (.38") | 12/4 (.61") | 14/2 (.42") | 10/3 (.61") | 50 | 500 | |
| | | | Solid TFN or THHN | | | | | | |
| | | | 18/2 (.41") | 14/2 (.61") | Solid Twisted Pair | | | | |

E-Z Lock® Connectors - Steel



AMC-50



AMC-5075



AMC-52

Used to connect AC/MC cable or flexible metal conduit to box or enclosure. Use slotted, Phillips or Robertson head screwdriver. Refer to the cable connector compatibility charts in the technical guide section for MCI-A and other cables. Use with anti-short bushing. Patented. US Patent D360,188.

 File No. E20534

Zinc Plated Steel / Insulated Throat - 105°C

| Catalog Number | Trade Size | K.O. Size | AC/MC Cable Range | | Throat Opening | Unit Qty. | Std. Pkg. |
|-------------------|---------------|--------------|----------------------|-------------|-------------------|--------------|--------------|
| | | | Min. | Max. | | | |
| AMC-50 | 3/8" | 1/2" | 14/2 (.40") | 10/3 (.62") | .406" | 50 | 500 |
| AMC-5075 | 1/2" | 1/2" | 10/4 (.62") | 6/4 (.92") | .565" | 25 | 250 |
| AMC-52 | 3/8" | 1/2" | 14/2 (.43") | 10/3 (.62") | .560" | 25 | 250 |
| AMC-75 | 3/4" | 3/4" | 10/3 (.566") | 6/3 (.81") | .560" | 25 | 100 |

 Quick Install