## **COMMERCIAL** STORAGE TANKS



## SMALL VOLUME JACKETED AND INSULATED

Designed for moderate, commercial peak demands, jacketed storage tanks are available in 80, 120 and 200 gallon capacities. They meet a variety of hot water requirements in smaller commercial applications where a large dump volume is required in a short period of time.

## **APPLICATIONS:**

Dormitories and laundry facilities

## **FEATURES:**

full descriptions are available in glossary beginning on page 33

- ASME Construction Available
- Designed for Storage of Potable Water to 180°F
- 80, 119, 200 Gallon Capacities
- Vitraglas® Lining
- Hand Hole Cleanout
- 2" NPT Dielectric Waterway Fittings (2½" on M-3-ST120R5A and M-3-ST200R5A)
- Optional 2" Rear Water Connections (only on M-3-ST120R5 and M-3-ST120R5A)
- Low Restriction Brass Drain Valve
- Side T&P Valve Opening
- Two Protective Magnesium Anode Rods
- 2" Non-CFC Foam Insulation
- 5–Year Limited Tank Warranty

Model Number	Capacity U.S. Gal.	Floor to Top of Heater in.	Jacket Dia. in.	Approx. Shipping Weight Ibs.
M-3-ST80R5	80	<b>58</b> <sup>3</sup> /4	24	192
M-3-ST80R5A*	80	58 <sup>3</sup> /4	24	278
M-3-ST120R5	119	<b>62</b> <sup>1</sup> / <sub>2</sub>	28	312
M-3-ST120R5A*	119	<b>62</b> <sup>1</sup> / <sub>2</sub>	28	366
M-3-ST200R5A*	200	77	32	541

\* Meets ASME code



