For Residential and Commercial Applications			
Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

# P1-\*\*DL/ P3-\*\*DL PEX Toilet Riser - One-Piece with Compression Sleeve or Insert

**Use:** For use in potable water distribution systems in accessible locations only

## **Design Features:**

- One-piece construction
- **Cut-to-Length** for a clean, professional installation
- 100% Compliant to California and Vermont "low-lead" requirements

# **Operating Specifications:**

40°- 180° F Temperature:

Pressure: 125 psi maximum

**Tubing Diameter:** 0.375" O.D. or 0.50" O.D.

MATERIAL SPECIFICATIONS		
Tube	Cross-linked Polyethylene (PEX)	
Compression Sleeve (3/8"OD)	POM	
Compression Insert (1/2"OD)	Stainless steel	



PART DIMENSIONS (Inches)			
Model	DIA. A	DIM. B	
P1-12DL	11.56	.38	
P1-15DL	14.56	.38	
P1-20DL	19.56	.38	

<b>PART DIMENSIONS</b> (Inches)		
Model	DIA. A	DIM. B
P3-15DL	14.56	.50
P3-20DL	19.56	.50

#### Part Listing:

P1-12DL	3/8" OD Tube x 11-1/2" Length
P1-12DL F	3/8" OD Tube x 11-1/2" Length, flag label
P1-15DL	3/8" OD Tube x 14-1/2" Length
P1-20DL	3/8" OD Tube x 19-1/2" Length
P1-20DL F	3/8" OD Tube x 19-1/2" Length, flag label
P3-15DL	1/2" OD Tube x 14-1/2" Length
P3-20DL	1/2" OD Tube x 19-1/2" Length
P3-20DL F	1/2" OD Tube x 19-1/2" Length, flag label

## **Listings & Certifications:**

- IAPMO listed to ASME A112.18.1 2005/CSA B125.1-05 (File # 0645)
- CSA approved to California Health & Safety Code and Vermont Bill S.152 (Project # 2174785)
- MerFlex PEX listed by NSF to ASME A112.18.6, CSA B125, CSA B137.5 and U.P. Code





