

**Features**

- Ideal in lighting, ductwork and other installation projects
- Cost-effective alternative to jack chain, threaded rod and associated hardware
- Safe working load of 20 kg (44 lb)
- Meets the fire rating requirements for DIN 4102-2 for 30 minutes at 30 percent of rated load
- 5:1 safety factor
- Sleek low-profile locking device reduces visual impact
- Adjustable after installation
- Available in stainless steel for applications where a higher level of corrosion resistance is required
- Works with a variety of CADDY® Fasteners



CADDY® SPEED LINK LD is a universal support system that quickly suspends static loads, even at an angle. It is a cost-effective alternative to jack chain, threaded rod and associated hardware in lighting, ductwork and other installation projects. The 1.5 mm (0.059 inch) wire rope with a crimped-on hook holds working loads of up to 20 kg (44 lb) with a 5:1 safety factor.

A small, aesthetically pleasing locking device completes the assembly. This low-profile stainless-steel device ensures stability and allows for additional adjustment after wire insertion. A small screwdriver releases the lock for fast installation adjustments.

The wire rope/hook assembly is available in galvanized steel as well as in stainless steel for applications where a higher level of corrosion resistance is required. The system installs without drilling or tools and allows objects to be hung at an angle – e.g., from sloped ceilings.

CADDY SPEED LINK LD is available in 2 m (6.6 ft), 5 m (16.4 ft) and 10 m (32.8 ft) lengths. It works with a variety of CADDY® Fasteners including beam clamps and purlin clips or can be looped directly around the beam.

This versatile support system can be used to hang lighting fixtures, ductwork, pipe, speakers, sensors and signage, among other things. A convenient plastic sleeve keeps the wire rope looped up until the contractor is ready to install. An optional extension tool allows CADDY SPEED LINK LD to be installed from the ground.

# CADDY® SPEED LINK LD

## Universal Support System



### CADDY® SPEED LINK LD

Wire rope diameter: 1.5 mm (0.059 inch)

Safe working load: 20 kg (44 lb)

| ARTICLE NUMBER | PART NUMBER | WIRE ROPE LENGTH  | MATERIAL         | QTY. PER BAG |
|----------------|-------------|-------------------|------------------|--------------|
| 195920         | SLD15L2     | 2m (6.6ft) long   | galvanized steel | 20           |
| 195925         | SLD15L5     | 5m (16.4ft) long  | galvanized steel | 20           |
| 195930         | SLD15L10    | 10m (32.8ft) long | galvanized steel | 20           |
| 195935         | SLD15L2S    | 2m (6.6ft) long   | stainless steel  | 2            |
| 195940         | SLD15L5S    | 5m (16.4ft) long  | stainless steel  | 2            |
| 195945         | SLD15L10S   | 10m (32.8ft) long | stainless steel  | 2            |



The ERICO® web site contains an aid to determine the length of the CADDY SPEED LINK necessary for a specific application.

### CADDY® Toggles

A new universal toggle and Y-toggle for CADDY SPEED LINK LD makes lighting and overhead decking installation even easier. For overhead decking applications, a universal toggle/wire rope assembly is now available in 2 m (6.6 ft), 5 m (16.4 ft) and 10 m (32.8 ft) lengths. The part is identical to standard CADDY SPEED LINK LD, except the hook is replaced with a toggle. An optional Y-toggle easily hangs lights. It consists of a 500 mm (20 in.) or 800 mm (31 in.) length of wire rope with a toggle on each end. The center of the wire rope is looped and crimped.

| PART NUMBER | DESCRIPTION                                          | UPC CODE 782856 | BOX                | WEIGHT PER BOX (LBS.) | WEIGHT PER BOX (KG.) |
|-------------|------------------------------------------------------|-----------------|--------------------|-----------------------|----------------------|
| SLD15Y500   | CADDY SPEED LINK Y-Toggle; 500 mm (20 in) leg length | 58417           | 20/bag; 5 bags/box | 4.0                   | 1.8                  |
| SLD15Y800   | CADDY SPEED LINK Y-Toggle; 800 mm (32 in) leg length | 58418           | 20/bag; 5 bags/box | 4.5                   | 2.0                  |
| SLD15L2T    | CADDY SPEED LINK Toggle; 2 m (6.6 ft) long           | 58419           | 20/bag; 5 bags/box | 8.7                   | 4.0                  |
| SLD15L5T    | CADDY SPEED LINK Toggle; 5 m (16.4 ft) long          | 58420           | 20/bag; 5 bags/box | 17.7                  | 8.0                  |
| SLD15L10T   | CADDY SPEED LINK Toggle; 10 m (32.8 ft) long         | 58421           | 20/bag; 5 bags/box | 27.7                  | 12.6                 |



Wire rope: 1.5 mm (0.059 in.) dia.

### CADDY SPEED LINK Tools and Accessories

| ARTICLE NUMBER | PART NUMBER | DESCRIPTION                       | BOX QTY | WEIGHT PER BOX (LBS.) | WEIGHT PER BOX (KG.) |
|----------------|-------------|-----------------------------------|---------|-----------------------|----------------------|
| 195851         | SLADCP      | Air Duct Corner Protector         | 10      | 0.7                   | 0.3                  |
| 195852         | SLADS       | Air Duct Support Attachment       | 100     | 1.3                   | 0.6                  |
| 195853         | SLWC        | Wire Cutter                       | 1       | 0.7                   | 0.3                  |
| 195859         | SLWPT       | Wire Insulation Protection Tube   | 25 m    | 3.8                   | 1.7                  |
| 195860         | SL1214      | Cable Clip 12-14 mm               | 100     | 1.1                   | 0.5                  |
| 195861         | SL1518      | Cable Clip 15-18 mm               | 100     | 1.2                   | 0.6                  |
| 195863         | SLLC250*    | Lighting Clip, 6 mm               | 200     | 1.5                   | 0.6                  |
| 195854         | SLEBM6      | Eye Bolt M6; 30 mm long           | 100     | 3.3                   | 0.7                  |
| 195856         | SLEBM8      | Eye Bolt M8; 40 mm long           | 100     | 2.5                   | 1.4                  |
| 195858         | SLEBWS      | Eye Bolt for Wood; H6, 60 mm long | 100     | 1.2                   | 1.1                  |

\* 22,5 kg ultimate static load limit



#### WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright ©2006 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

Phone: 800-333-0852

Fax: 800-677-5403

[www.erico.com](http://www.erico.com)



FM493S

FM1213LT05EN

00325M6