


**4 IN. SQUARE WELDED BOXES - 1-1/2 TO 2-1/8 IN. DEEP WITH NONMETALLIC SHEATHED CABLE CLAMPS**

4 in. Square Boxes, 1-1/2 in. Deep - Welded with Nonmetallic Sheathed Cable Clamps

A19



Catalog #: 211

APPLICATIONS

RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles
Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices

PRODUCT FEATURES

Combination screw heads provide for faster installation
TKO® Knockouts offer greater flexibility with RACO patented combination 1/2" and 3/4" knockout
N/A

UL LISTED

File E195978

COMPLIANCE

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com
600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System: Nonmetallic Sheathed Cable
Country of Origin: USA

CONFIGURATION

Cable Priouts: 4
Bracket Type: No Bracket
Drawn or Welded: Welded
Raised Ground: No
Side Knockout(s): (4) 1/2 in. & (2) TKO®
Bottom Knockout(s): (1) 1/2 in.

DRAWING DIMENSIONS

Dimension A: 1-1/2 in.

PRODUCT MEASUREMENTS

Depth: 1-1/2 in.
Cubic Inches (cm³): 21.0 (344.1)
Wt. Ea. (Lbs.): 0.771
Product Length (in.): 1.563
Product Width (in.): 4
Product Height (in.): 4

PACKAGING

Minimum Pack Qty.: 50
Std. Pkg.: 50
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 77.1
Ship Carton Length (in.): 20.25
Ship Carton Width (in.): 8.5
Ship Carton Height (in.): 10.25
Ctn Weight (Lbs.): 38.55
Pallet Qty: 2500
UPC Number: 050169902110
I2of5: 50050169902115