

ProLED S14 Sign Lamp

Specifications

- Designed for rapidly flashing sign applications
- Dimmable
- Wet Location Rated
- Red, Blue, Green, Yellow, White, Orange and Clear 2700K option
- Unique "Heat-to-Base" technology
- Omnidirectional distribution
- No Mercury or UV/IR emissions
- RoHS Compliant
- 5-Year Limited Warranty

Markets & Applications



Commercial



Retail



Outdoor

Ordering Information



Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CRI	Lumens	Useful Life*	Pkg. Qty.	MOL
1.4 Watt	Med.	80517	S14RED1C/LED	Red	120	-	-	-	40000	1/25	3.35"
1.4 Watt	Med.	80518	S14BLU1C/LED	Blue	120	-	-	-	40000	1/25	3.35"
1.4 Watt	Med.	80519	S14GRN1C/LED	Green	120	-	-	-	40000	1/25	3.35"
1.4 Watt	Med.	80520	S14YEL1C/LED	Yellow	120	-	-	-	40000	1/25	3.35"
1.4 Watt	Med.	80521	S14WH1C/LED	White	120	-	-	-	40000	1/25	3.35"
1.4 Watt	Med.	80522	S14CL1C/827/LED	Clear	120	2700	82	35	40000	1/25	3.35"
1.4 Watt	Med.	80523	S14ORG1C/LED	Orange	120	-	-	-	40000	1/25	3.35"

* Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point at decreased light levels. Not for use in enclosed fixtures.