

# WP5000 Extra-Duty Plastic Series

Extra-Duty Plastic Weatherproof Covers are easy to install and shipped with an adhered gasket, mounting screws, base, cover assembly, and inserts for a variety of applications.



## FEATURES

- Complies with 2014 Article 406.9(B)(1) for wet locations and extra-duty applications
- Meets requirements for cold impact testing: -60° F (-51° C)
- 5000, 5100, 5200 Series available in 10 different colors
- 5500 Series available in Clear, Gray, and Yellow
- Heavy-duty UV stabilized polycarbonate construction ensures long-lasting durability
- Lockable hasp: All models accept up to 0.25" dia shank
- Impact rated: 12 lb impact test to ensure cover remains intact
- Single gang covers mount vertically or horizontally
- Single Gang Models:
  - 3 inserts provided with all models that allow each model to meet multiple installations (up to 16 configurations)
- Double Gang Models:
  - 6 inserts provided with all models that allow each model to meet multiple installations (up to 70 configurations)
  - 2 round inserts accommodate from 1.375" to 2.656" plugs for the 30/50 amp applications (4-3/4" depth)
- Reinforced hinge pin – designed to exceed 40 lb hinge hang/stress test

## RATINGS

### Cover:

UV stabilized polycarbonate

UL Certified for Type 3R

Outdoor Enclosures:

Single Gang:

Horizontal – 3 cord outlets 0.5" wide by 0.9" high

Vertical – 1 cord outlet 0.75" wide by 0.9" high

Double Gang:

– 1 cord outlet 1.50" wide by 1.25" high 30/50 amp

– 1 cord outlet 1.1" wide by 3.0" high

### Mounting Base and Inserts:

UV stabilized polycarbonate

### Gasket:

Neoprene – 1/8" (4.8 mm) thick with slits for mounting screws

### Max Cord Size:

Single Gang – (2) 14 gauge or (1) 12 gauge

Double Gang – (2) 12 gauge or (1) 10 gauge

30/50 Amp Double Gang – (1) 6 gauge (3 wire ground)

**Warranty:** Limited 1 year

## Extra-Duty Plastic Weatherproof Covers Ordering



Depth	Height	Width	Type	Hinge	Flexi-Guard Inserts	Standard Colors		Additional Colors		
						Clear/Gray	Gray	Black	White	Green
2.25	6.5	4.75	Single Gang	Vertical/Horiz	WP17	WP5000C	WP5000G	WP5000BL	WP5000W	WP5000GN
2.75	6.5	4.75	Single Gang	Vertical/Horiz	WP17	WP5100C	WP5100G	WP5100BL	WP5100W	WP5100GN
3.625	6.5	4.75	Single Gang	Vertical/Horiz	WP17	WP5110C	WP5110G	WP5110BL	WP5110W	WP5110GN
2.25	6.5	6.5	Double Gang	Vertical	WP217	WP5220C	WP5220G	WP5220BL	WP5220W	WP5220GN
2.75	6.5	6.5	Double Gang	Vertical	WP217	WP5225C	WP5225G	WP5225BL	WP5225W	WP5225GN
3.625	6.5	6.5	Double Gang	Vertical	WP217	WP5240C	WP5240G	WP5240BL	WP5240W	WP5240GN
30/50 AMP*	6.5	6.5	Double Gang	Vertical	WP107, WP213	WP5500C	WP5500G	—	—	—

\* 30/50 AMP = 4-3/4" depth



Depth	Height	Width	Type	Hinge	Flexi-Guard Inserts	Building Facade Colors			Safety Colors	
						Beige	Bronze	Red	Yellow	Orange
2.25	6.5	4.75	Single Gang	Vertical/Horiz	WP17	WP5000B	WP5000BR	WP5000R	WP5000Y	WP5000OR
2.75	6.5	4.75	Single Gang	Vertical/Horiz	WP17	WP5100B	WP5100BR	WP5100R	WP5100Y	WP5100OR
3.625	6.5	4.75	Single Gang	Vertical/Horiz	WP17	WP5110B	WP5110BR	WP5110R	WP5110Y	WP5110OR
2.25	6.5	6.5	Double Gang	Vertical	WP217	WP5220B	WP5220BR	WP5220R	WP5220Y	WP5220OR
2.75	6.5	6.5	Double Gang	Vertical	WP217	WP5225B	WP5225BR	WP5225R	WP5225Y	WP5225OR
3.625	6.5	6.5	Double Gang	Vertical	WP217	WP5240B	WP5240BR	WP5240R	WP5240Y	WP5240OR
30/50 AMP*	6.5	6.5	Double Gang	Vertical	WP107, WP213	—	—	—	WP5500Y	—

\* 30/50 AMP = 4-3/4" depth

### Additional skus available:

- **WP5103C – WP5100C** with round adapter plate
- **WP5221C** – 2-1/4" depth double gang with WP101 (double gang duplex) and WP102 (double gang GFCI) inserts
- **WP10HP** – 10/pack stainless steel hinge pins