

60 A Control System with Type 3R Load Center

T21000R Series

This system can be used as a load center only, or add a heavy-duty mechanical time switch or wiring devices for a complete system.

Applications

- Pool/Spa Equipment • Lights

Features

- Four breaker spaces
- Accepts PF1000M, P1403ME, P1353ME, P4043ME, P4243ME, T100M or RC2000M Series mechanisms
- Accepts many interchangeable type breakers
- Load center dead front has two knockouts for switches or GFCIs and one on the side
- Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately

Model #	Mechanism	Switch Type	Mechanism Supply Voltage
T21000R	Load Center Only	—	—
T21001R	T101M	SPST	120 VAC, 60 Hz
T21004R	T104M	DPST	240 VAC, 60 Hz

Accessories/Replacements

Extra/replacement trippers 1 ON and 1 OFF	156T1978A
Insulator for Timers	124T1952
Spacer-Standoff, 3" Long - 2 Pack	21T166A
Spacer-Standoff, 3" Long - 4 Pack	21T156A
In-Use Weatherproof Cover	WP1000C



Ratings	
Load Center Rating	60 A, 120/240 VAC or 120/208 VAC, Single Phase
Resistive	40 A, 120-240 VAC, 60 Hz
Inductive	40 A, 120-240 VAC, 60 Hz
Tungsten	40 A, 120-240 VAC, 60 Hz
Pilot Duty	1000 VA, 120-240 VAC, 60 Hz
Motor	5 HP, 28 FLA @ 240 VAC, 60 Hz; 2 HP, 24 FLA @ 120 VAC, 60 Hz
Operating Temperature	-40° F to 130° F (-40° C to 54° C)
Dimensions	16.875" x 8.875" x 4.75"
H x W x D	(428.6 mm x 225.4 mm x 120.7 mm)
Knockout Dimensions	
Bottom	(5) combination ½" - ¾" and (3) combination ¾" - 1"
Left	(1) combination ½" - ¾"
Back	(1) combination ½" - ¾" and (1) ¾" - 1"
Right	(1) 1 ¾" x 2 ¾"
Warranty	1-year