

In-Wall Timers

Electronic Countdown Timers



EI400WC



White



Ivory



Light Almond



| Ratings | |
|-----------------------|---|
| Operating Voltage | 120-277 VAC, 50/60 Hz |
| Resistive | 20 A, 120-277 VAC, 50/60 Hz |
| Incandescent | 15 A, 120 VAC, 50/60 Hz; 6 A, 208-277 VAC, 50/60 Hz |
| Inductive Ballast | 16 A, 120-277 VAC, 50/60 Hz |
| Motor | 1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC 50/60 Hz |
| DC Loads | 4 A, 12 VDC; 2 A, 28 VDC |
| Operating Temperature | 32° F to 122° F (0° C to 50° C) |
| Dimensions H x W x D | 4.125" X 1.75" X 1.1875" (104.8mm x 44.5mm x 30.2mm) |
| Warranty | 5-year limited |

Note: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

EI400 Series

Programmable Electronic Countdown Timer

Offering a programmable countdown time between one second and 24 hours, this versatile timer can handle any application, regardless of load type. No neutral connection is required.

Features

- Programmable countdown time interval from one second to 24 hours
- Settings stored in non-volatile memory
- Optional audible and/or visual warning of impending load switch OFF
- Lockable settings help avoid unintended changes
- Single-pole or 3-way switch compatible installation
- Incandescent/fluorescent/CFL/LED compatible
- Isolated switch allows timer to be used with any load type including AC and DC loads
- Replaceable CR2 lithium battery provides up to three years of operation
- No neutral wire connection enables easy retrofitting and quicker installation
- 24-hour programming allows for continuous operation

| White | Ivory | Light Almond |
|----------------|---------------|-----------------|
| EI400WC | EI400C | EI400LAC |

Note: For use with standard decorator plate, not included

Countdown Timer Applications

- Bathroom fans • Spas • Hot tubs • Storage closets • Garage lights

