



SDS-plus Standard Tip



SDS-plus Standard Tip Features:

- Fits all SDS-plus and Hilti TE-C rotary hammers
- Reduced area above the flute prevents the drill bit from binding while drilling-the full usable length can be utilized
- Chrome vanadium shaft through-hardened to 50-53HrC
- Patented tip and flute design removes dust more efficiently - up to 25% faster than other bits
- Shot-peened, double-tempered finish reduces breakage
- Hot isostatically pressed to extend life and resist breakage
- Copper braze material gives high heat resistance for reduced tip loss
- All tips made to ANSI specifications

Item #	Diameter	Twist Length	Overall Length
	5/32"		
322001	5/32"		4"
322002	5/32"		6"
322002B25	3/16"	2"	6"
322003	3/16"	4"	6"
322003B25	3/16"	4"	4"
322004	3/16"	2"	4"
322004B25	3/16"	2"	6"
322005	3/16"	4"	6"



322006	3/16"	4"	8"
322006B25	3/16"	6"	10"
322007	3/16"	8"	10"
322007B25	7/32"	8"	12"
322013	7/32"	10"	12"
322013B25	7/32"	10"	6"
322015	7/32"	4"	6"
322015B25	1/4"	4"	12"
322016	1/4"	10"	12"
322016B25	1/4"	10"	4"
322017	1/4"	2"	4"
322017B25	1/4"	2"	6"
322018	1/4"	4"	6"
322018B25	1/4"	4"	8"
322019	1/4"	6"	8"
322020	1/4"	6"	10"
322021	5/16"	8"	12"
322022	5/16"	10"	14"
322022B25	5/16"	12"	6"
322023	3/8"	4"	6"
322024	3/8"	4"	12"
322024B25	3/8"	10"	6"
322025	3/8"	4"	6"
322026	3/8"	4"	10"
322026B25	3/8"	8"	12"
322027	3/8"	10"	12"
322028	7/16"	10"	18"
322029	1/2"	16"	24"
322031	1/2"	22"	6"
322031B25	1/2"	4"	6"
322032	1/2"	4"	6"
322033	1/2"	4"	10"
322033B25	1/2"	8"	12"
322034	1/2"	10"	12"