WHITLAM

BLUE MAGIC INDUSTRIAL GRADE

Pipe Thread Compound

BLUE MAGIC is an all purpose, non-seizing, industrial grade thread sealing compound that produces a leak-proof seal on all types of plastic and metal (including stainless steel) threaded connections. **BLUE MAGIC** is a smooth, grit free, completely homogenized, blue industrial grade paste.

- Non-Separating
- Grit Free Paste
- Adheres to Oily Threads
- Safe for PVC & CPVC
- Nontoxic
- Superior Anti-Galling Properties

PRESSURE RANGE USE:

Approved for SPEARS® & IPEX

FOR USE ON THREADED: ABS, PVC, CPVC, Delrin*, Zytel*, Fiberglass, Nylon, Polypropylene,

Polybutylene, Polyethylene,

Celcon**, Cycolac***, and all

Gases:

Fittings

types of metal.

Up to 3,000 PSI (211 kg/cm²) Liquids:

Up to 6,000 PSI (422 kg/cm²)

TEMPERATURE RANGE USE:

-50°F (-46°C) to 400°F (+204°C)

U.S. FEDERAL SPECIFICATIONS

Blue Magic exceeds TT-S-1732

AVAILABLE SIZES

Stock# Size IG2 2 oz. tube (.056 kg) IG4 1/4 pint (118 ml) IG8 1/2 pint (237 ml) IG8A[†] 1/2 pint (237 ml) **IG16** 1 pint (473 ml) **IG32** 1 quart (.95 L) IG1 1 gal. (3.785 L) IG5 5 gal. (18.9 L) **IG55** 55 gal. (208 L)

- *Dupont registered trademarks
- **Celanese registered trademark
- ***General Electric Plastics registered trademark
- † IG8A is packaged in a display box
- J.C. Whitlam Manufacturing Co. P.O. Box 380 Wadsworth, OH 44282



U.S. & Canada Phone: 800-321-8358 FAX: 800-537-0588

: 800-537-0588 International

Phone: 330-334-2524 FAX: 330-334-3005

www.joinpipe.com Email: info@jcwhitlam.com

Suitable for use on systems carrying:

Acids, Dilute
Air, Compressed
Aliphatic Solvents
Alkalis, Dilute
Ammonia
Brine
Butane
Carbon Dioxide
Castor Oils
Caustic Alkali, Dilute
Chlorinated Water
Coal Tar Naphtha
Corrosives
Cutting Oils

Diesel Fuel Oil
Fatty Acids
Freons (All)
Gasohol
Gasoline
Glycol
Heating Oils
Helium, Gaseous
Hydraulic Oils
Hydrogen
Inert Gases
Jet Fuel
Kerosene

LP Gases
Lacquer
Mineral Oils
Naphtha
Natural Gas
Nitrogen Gas
Petroleum Oils
Petroleum Solvents
Potable Water

Propane
Refrigeration
Gases
Soap, Liquid
Steam Lines
Sugar, Liquid
Vegetable Oils
Water
Xylol



NSF Standard 14 NSF Standard 61 pw-G/dwv/sw



Underwriters' Laboratories of Canada Listed for Natural Gas, Gasoline, Petroleum Oils, Propane & Butane

"For a Positive Leak-proof Seal"

Distributed By:



