





Down-Lites | Trims for IC1LEDG4, IC1RLEDG4, IC1LWDG4N, IC1RLWDG4N, IC91LEDG4, IC91RLEDG4, IC91LWDG4 & IC91RLWDG4


Downlight

	Catalog # 14W-WH 14B-WH 14B-BL 14B-ABZ 14B-SC	Description White Baffle, White Trim Black Baffle, White Trim Black Baffle, Black Trim Black Baffle, Classic Aged Bronze Black Baffle, Satin Chrome Trim	Aperture 3 3/8"		
---	---	--	---------------------------	---	---

Baffle


	Catalog # 17B-WH 17C-WH 17G-WH 17HZ-WH 17PT-SC 17W-WH 17WHZ-WH 17WHZ-ABZ	Description Black Alzak®, White Trim Clear Alzak®, White Trim Gold Alzak®, White Trim Haze, White Trim Pewter Alzak®, Satin Chrome Trim Gloss White, White Trim Wheat Haze, White Trim Wheat Haze, Classic Aged Bronze	Aperture 3 3/8"		
---	---	---	---------------------------	---	---

Cone


	Catalog # 13-WH	Description White Trim	Aperture 2"		
---	---------------------------	----------------------------------	-----------------------	--	---

Pinhole with Integral Shield

Lensed


	Catalog # 11-WH	Description Drop Opal Lens Trim			
---	---------------------------	---	--	---	---

Drop Opal

	Catalog # 12W-ABZ 12W-SC 12W-WH	Description Perimeter Frosted Lens, Classic Aged Bronze Trim Perimeter Frosted Lens, Satin Chrome Trim Perimeter Frosted Lens, White Trim			
---	---	---	--	---	---


Frosted Lens with Clear Center

Wall Wash

	Catalog # 39C-WH 39W-WH 39HZ-WH 39WHZ-WH	Description Clear Alzak®, White Trim Gloss White, White Trim Haze, White Trim Wheat Haze, White Trim			
---	---	---	--	---	---

Lensed Wall Wash Cone

Hyperbolic

	Catalog # 17HYP2-C-WH 17HYP2-B-WH ¹ 17HYP2-W-WH 17HYP2-HZ-WH 17HYP2-WHZ-WH ¹ 17HYP2-WHZ-ABZ ¹	Description Clear Alzak®, White Trim Black Alzak®, White Trim White, White Trim Haze, White Trim Wheat Haze, White Trim Wheat Haze, Classic Aged Bronze Trim	Aperture 3 3/8"		
---	---	---	---------------------------	---	---

Cone

¹Not ENERGY STAR® Qualified or T24 certified










Certified to the high efficiency requirements of California T24



UL listed for use in wet location.

ENERGY STAR® qualification and T24 certification is dependent on trim finish and LED color temperature. See housing spec sheet on www.junolightinggroup.com for specific information for each trim.

Downlight

	Catalog # 14W-WH 14B-WH 14B-BL 14B-ABZ 14B-SC	Description White Baffle, White Trim Black Baffle, White Trim Black Baffle, Black Trim Black Baffle, Classic Aged Bronze Black Baffle, Satin Chrome Trim	Max. Lamp Rating ICPL426/PL426: 26W CFL ICPL418/PL418: 18W CFL Aperture 3 3/8"	
	Catalog # 140W-WH 140B-WH Optimized for CFL	Description White Baffle, White Trim Black Baffle, White Trim	Max. Lamp Rating ICPL426/PL426: 26W CFL ICPL418/PL418: 18W CFL Aperture 3 3/8"	
	Catalog # 17B-WH 17CLI-WH 17G-WH 17HZ-WH 17PT-SC 17W-WH 17WHZ-WH 17WHZ-ABZ	Description Black Alzak®, White Trim Clear, Low Iridescent Alzak®, White Trim Gold Alzak®, White Trim Haze, White Trim Pewter Alzak®, Satin Chrome Trim Gloss White, White Trim Wheat Haze, White Trim Wheat Haze, Classic Aged Bronze	Max. Lamp Rating ICPL426/PL426: 26W CFL ICPL418/PL418: 18W CFL Aperture 3 3/8"	
	Catalog # 170CLI-WH 170HZ-WH 170WHZ-WH Optimized for CFL	Description Clear, Low Iridescent Alzak®, White Trim Haze, White Trim Wheat Haze, White Trim	Max. Lamp Rating ICPL426/PL426: 26W CFL ICPL418/PL418: 18W CFL Aperture 3 3/8"	
	Catalog # 13-WH	Description White Trim	Max. Lamp Rating ICPL426/PL426: 26W CFL ICPL418/PL418: 18W CFL Aperture 2"	
Lensed				
	Catalog # 11-WH* *Not for use with ICPL413RE or ICPL418RE	Description Drop Opal Lens, White Trim	Max. Lamp Rating ICPL426/PL426: 26W CFL ICPL418/PL418: 18W CFL	  
	Catalog # 12W-ABZ 12W-SC 12W-WH	Description Perimeter Frosted Lens, Classic Aged Bronze Trim Perimeter Frosted Lens, Satin Chrome Trim Perimeter Frosted Lens, White Trim	Max. Lamp Rating ICPL426/PL426: 26W CFL ICPL418/PL418: 18W CFL	  

AIR-LOC Juno IC housings meet IECC Air-Loc® Code requirements per ASTM E283. Air-Loc® rated trims are pre-gasketed for minimum air leakage with IC housings.

 UL listed for use in wet location.


Adjustables (cont)



Adjustable Slot Aperture

Catalog #
445-WH
Description
White Trim
Not for use with IC1/IC1S/IC1W housings


Max. Lamp Rating
IC1P: 50W MR16/ES16
120V GU10 base*
TC1/TC1R/TC1RCWN: 50W
MR16/PAR16/ES16
120V GU10 base*
Aperture
1 1/2" x 2 1/8" Oblong
Adjustment
40° vertical



Eyeball with Black Baffle

Catalog #
448-WH
Description
White Eyeball with Black Baffle,
White Trim

Max. Lamp Rating
IC1: 35W MR16/ES16
120V GU10 base*
IC1P: 50W MR16/ES16
120V GU10 base*
TC1/TC1R/TC1RCWN: 50W
MR16/PAR16/ES16
120V GU10 base*
Adjustment
35° vertical



Lensed




Frosted Lens with
Clear Center

Catalog #
12W-ABZ
Description
Perimeter Frosted Lens,
Classic Aged Bronze Trim
12W-SC
Perimeter Frosted Lens,
Satin Chrome Trim
12W-WH
Perimeter Frosted Lens,
White Trim

** requires T599 Socket Extender (see Accessories)


Max. Lamp Rating
IC1: 30W R20, 50W PAR20**
IC1P: 50W PAR20/R20,
40W K19
TC1/TC1R: 50W
PAR20/R20
TC1RCWN: 50W
PAR20



Drop Opal

Catalog #
11-WH
Description
Drop Opal Lens, White Trim

Max. Lamp Rating
IC1: 30W R20, 35W PAR20
IC1P: 30W R20, 50W
PAR20, 40W K19
TC1/TC1R: 50W
PAR20/R20
TC1RCWN: 50W
PAR20




Wall Wash



Adjustable Scoop

Catalog #
16-WH
Description
White Trim



Max. Lamp Rating
IC1/IC1P/TC1/TC1R:
40W R14
40W R16
intermediate screw base
Adjustment
50° vertical



Adjustable Scoop

Catalog #
446-WH
Description
White Trim
Not for use with IC1/IC1S/IC1W housings

Max. Lamp Rating
IC1P: 50W MR16/ES16
120V GU10 base*
TC1/TC1R/TC1RCWN:
50W MR16/PAR16/ES16
120V GU10 base*
Adjustment
40° vertical



UL listed for use
in wet location.