

Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

DESCRIPTION

- · Metal construction with various finishes identified by suffix
- Flexible supplies with 3/8" compression fittings
- Includes matching finish side spray with Hydrolock® quick connect system
- Hydrolock® quick connect installation

OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel

FLOW

• Spout flow is limited to 2.0 gpm (7.6 L/min) at 60 psi

CARTRIDGE

• 1255™ Duralast™ cartridge


STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1 and all applicable requirements therein including NSF 61/9
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

Specifications



Models: S711 series

9-3/8" (238mm) 4" 12-1/4" (102mm) (102mm) (311mm) 3-7/16" (87mm) 8-1/2" (216mm) ESCUTCHEON DIAMETER 4-7/8" 5-7/16" (138mm) **FULL OPEN** (124mm) 4-1/8" (105mm) ESCUTCHEON DIA CLOSED 2-1/4" (57mm) MAX. **DECK THICKNESS** 32-1/2" (826mm) **QUICK CONNECT** 囲 **NOTE: MINIMUM DIA. HOLES FOR INSTALLATION** Spout = 1-1/4'' (32mm) Handle = 1-1/4'' (32mm)**Side Spray = 1" (25mm)** The use of aerator part 116711 reduces flow to a maximum of CRITICAL DIMENSIONS 1.5 gpm (5.7L/min.) (DO NOT SCALE)