## ACCENT LIGHT ACCESSORIES



P8611-31 Black 45° cube cell louver fits under supplied glass lens. SIZE: 3-1/2" cube cell for P5234-31 & P5236-31.

P8613-31 Black 45° cube cell louver fits under supplied glass lens. SIZE: 4-3/4" cube cell for P5235-31 & P5237-31



## P8612-31 Black

Light shields adjust to desired length on cowling of light fixture. Rotate bias-cut end to adjust cutoff angle.

SIZE: 5-3/4" long for P5234-31 & P5236-31

P8614-31 Black

Light shields adjust to desired length on cowling of light fixture. Rotate bias-cut end to adjust cutoff angle.

SIZE: 7-1/4" long for P5235-31 & P5237-31

## ACCESSORIES FOR INSTALLATION



P8527-01 Direct burial in-ground 12-Volt electronic transformer. Stainless steel housing. Internal and external fittings provided. 100w capacity. SIZE: 3-5/8" W., 8-5/8" length, 3-3/8" ht.



12-Volt Cable 2 conductor. Black. UL listed. P8635-31 10-gauge 300 ft.

P8628-31 12-gauge 100 ft.
P8699-31 12-gauge 200 ft.



P8672-31 Black Miniature pedestal mount. Powder-coat painted cast metal. Flanged base for surface mounting. 1/2 NPS thread. SIZE: 1-1/2" dia., 1" ht.



P8659-01 Adjustable mounting bracket for low voltage installations. Flexible, stainless steel band adjusts to wrap around tree limbs, poles, etc. from 2" to 6" diameter. Includes "L" bracket and 1/2" stem nut. Wire nuts included.



P8671-31 Black Polycarbonate canopy for tree trunks and walls. 1/2 NPS thread. SIZE: 4-1/8" dia. Extends 1-3/16".



MOUNTING STEMS 1/2 NPS THREADS

16" STEM P8666-31 Black P8666-38 Green

8-1/2" STEM P8667-31 Black P8667-38 Green



P8673-31R Black For more permanent burial connection. 120 or 12-volt gel-filled direct burial. UL listed. Accepts 10ga to 18ga awg wires.



P8618-31 Black Ground stake, 8-3/4" ABS movable stake for direct mounting of 12v landscape lights. 1/2 NPS thread.



P8708-01 Silicone filled Underground direct burial wire connectors. #20-#10 gauge. 10 per pack (1 standard pack = 10 pieces). Size: 1-3/4" L., 5/8" dia.



P8562-31 Black
Quick-mount landscape post for
120v or 12v PVC.
SIZE: 3" dia., 20" length with stabilizing
grid and post.
1/2 NPS threaded hole. Wet
location UL listed.



P8651-01 Black Low voltage Quick-connector. Allows #10 or #12 gauge outdoor low voltage cable to connect to an 18 gauge wire from fixture. SIZE: 1-5/8" W., 5/8" ht.





PRODUCT WATT BEAM SPREAD

P8663-01 20w 25°
P8665-01 50w 25°
Halogen Reflector Lamps for P5236-31
Spotlight D.C. bayonet base.



P7801-01 Lamp 18w T5 wedge base lamp