


4 IN. SQUARE WELDED BOXES - 1-1/2 TO 2-1/8 IN. DEEP WITH NONMETALLIC SHEATHED CABLE CLAMPS

4 in. Square Boxes, 2-1/8 in. Deep - Welded with Nonmetallic Sheathed Cable Clamps 600V

A19





Catalog #: 242

APPLICATIONS

RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles Square boxes are used where multiple conductor runs are split into two or more directions to bring power to a number of electrical devices

PRODUCT FEATURES

Combination screw heads provide for faster installation

TKO® Knockouts offer greater flexibility with RACO patented combination 1/2" and 3/4" knockout N/A

UL LISTED

File F195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com 600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Nonmetallic Sheathed Cable Wiring System:

CONFIGURATION

Cable Priouts: No Bracket Bracket Type: Drawn or Welded: Welded No Raised Ground:

(4) 1/2 in. & (2) TKO® (1) 1/2 in. Side Knockout(s)

Bottom Knockouts(s):

DRAWING DIMENSIONS

2-1/8 in. Dimension A:

PRODUCT MEASUREMENTS

2-1/8 in. Depth: Cubic Inches (cm3): Wt. Ea. (Lbs.): 30.3 (496.5) 0.946 Product Length (in.): Product Width (in.): 4 00 Product Height (in.): 4.00

PACKAGING

Minimum Pack Qty.: 25 Std. Pkg.: Product UPC-A Labeled: 25 Nο Weight (Lbs. Per/C): 94.60 Ship Carton Length (in.): Ship Carton Width (in.): 19.00 9.00 Ship Carton Height (in.): 7.75 Ctn Weight (Lbs.): 23.65 Pallet Qty: 1750

UPC Number: 050169002421 50050169002426 12of5