

CERTIFIED LEAD FREE
500 SB Series



CERTIFIED LEAD FREE
Check Valve

- Silicon bronze cast body.
- Silicon bronze cast poppet.
- Female threads.

Part No.	Size	Weight Each lbs.	Carton Quantity
501SB	1/2	.6	1
502SB	3/4	.8	1
503SB	1	1.1	1
513SB*	1	1.2	1
504SB	1 1/4	1.6	1
514SB**	1 1/4	1.7	1
505SB	1 1/2	2.1	1
506SB	2	3.7	1
507SB	2 1/2	9.8	1
508SB	3	10.8	1
509SB	4	23.6	1
510SB***	5	25.1	1
511SB	6	41.5	1

513SB* has longer threads.
514SB** has longer threads.
510SB*** has 5" male threads both ends.

CERTIFIED LEAD FREE
2500 SB Series



CERTIFIED LEAD FREE
Stemless Check Valve

- Silicon bronze cast body.
- Silicon bronze stemless poppet.
- Female threads.

Part No.	Size	Weight Each lbs.	Carton Quantity
2503SB	1	1.3	1
2504SB	1 1/4	1.8	1
2505SB	1 1/2	2.1	1
2506SB	2	3.7	1



CERTIFIED LEAD FREE
Submersible Check Valve



- Silicon bronze cast body.
- Silicon bronze cast poppet.
- Female-Male threads.

Part No.	Size FxM	Weight Each lbs.	Carton Quantity
610SB**	1 x 1 Long	1.4	1
611SB**	1 1/4 x 1 1/4 Long	2.0	1
616SB	1 x 1	1.4	1
617SB	1 x 1 1/4	1.4	1
618SB	1 1/4 x 1 1/4	1.8	1
622SB	2 x 2	3.9	1
623SB	3 x 3	10.4	1
624SB	4 x 4	22.6	1
625SB	6 x 6	41.4	1

** Extended male and female threads

*Silicon bronze components contain less than .05% (1/20 of 1%) Lead.

Check Valves furnished with Buna-N O-Ring, stainless steel spring, stainless steel washer, and stainless steel locknut. All valves 1/2" through 1-1/2" have a working pressure of 400 psi. All valves 2" and larger have a working pressure of 600 psi. 190° Maximum Temperature Rating

MADE IN U.S.A.