Product data sheet Characteristics

HOM240GFI MINIATURE CIRCUIT BREAKER 120/240V 40A





Main

Man		Č
Product or component type	Miniature circuit-breaker	Christin
Range of product	Homeline	To. S
[In] rated current	40 A	SICIE
Product certifications	UL listed	e pro
[Ue] rated operational voltage	120/240 V AC	these
Mounting mode	Plug-in	It o
Poles description	2P	elab
Short-circuit current	10 kA	V OF 1
Number of spaces required	2	tabilit
Circuit breaker type	Ground fault protecting class A 6 mA	
Circuit breaker application	HACR rated	Juliu.
Electrical connection	Screw clamp terminals	dete
AWG gauge	AWG 12AWG 4 for 1 cable(s) (aluminium) AWG 14AWG 6 for 1 cable(s) (copper)	used tor
Height	3.13 in	o pe
Width	2 in	 not
Depth	2.98 in	 oue.

Offer Sustainability

Sustainable offer status	Green Premium product	(
RoHS (date code: YYWW)	Compliant - since 1340 - Schneider Electric declaration of conformity	- i
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	•
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Available	

Product Life Status	END-OF-SALE NOTICE
Product Life Status	END-OF-SALE NOTICE