Product data sheet Characteristics

QO120L125G LOAD CENTER QO MLO 240V 125A 1PH 20SP



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

			٠	
N	л	_	п	n
и۱	/1	~		

Commercial Status	Commercialised
Product or component type	Load Center
Range of product	QO
Load center type	Convertible Mains (lugs)
[In] rated current	125 A
Number of spaces	20
Short-circuit current	65 kA
Number of circuits	20
Number of tandem circuit breakers	0
Network number of phases	1 phase
[Ue] rated operational voltage	120/240 V AC

Complementary

AWG gauge	62/0 AWG aluminium/copper
NEMA degree of protection	NEMA 1 indoor
Cover type	Order separately
Device composition	Grounding bar included (not installed)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated copper busbar
Product certifications	UL listed

Ordering and shipping details

Category	00001 - QO 1PH LC,12-42 CKT,NEMA1	
Discount Schedule	DE3A	
GTIN	00785901847854	
Nbr. of units in pkg.	1	
Package weight(Lbs)	12.18	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS	Compliant - since 1248 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Period	18 mont
Period	18