# FIRE CLASSIFIED FLOOR BOXES
## Omnibox™ Series Floor Boxes

OmniBox Series Floor Boxes Metal Cover Plates Ordering Information

828R Brass Duplex Cover Plate

Flip lids. Can also be used with a 106 type communication adapter.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

828GFITC Brass GFI Cover Plate

May be used with Activate and Ortronics® Connectivity Systems in conjunction with 817B, 827B and 837B Flanges.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

828DPGFITC Brass Rectangular Cover Plate

Allows for mounting of a duplex-style receptacle with a rectangular-style flip lid cover.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

828COMTC Brass Communication Cover Plate

3 1/8" [80.2mm] 4 3/16" [106.2mm]

Allows for up to four communication devices to be mounted in a recessed position within the 880 Floor Box. The 828COM Cover Plate has removable slides for cable egress.

NOTE: For use with 880S and 880CS Series Boxes only.

828DLR
Brass Single Locking Receptacle Cover Plate

Single flip lid cover for 20A or 30A single locking receptacles. Device opening is 2 5/8" [67mm]. For use with maximum female locking device of 1.58" diameter and maximum male plug face of 2.25" diameter.

4 3/16" [106.2mm] 3 1/8" [80.2mm]

828SPTC Brass Duplex Cover Plate

Screw plugs. Screw plugs are 1 1/2" [38mm] in diameter.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

829STC Brass Communication Cover Plate

Data slides. Feed through only, not for use with a mounting plate for communication jacks.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

829CK Brass Communication Cover Plate

2 5/8" and 2 1/4" [67mm and 57mm] plugs.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

829CK-1 Brass Communication Cover Plate

2 5/8" and 1" [67mm and 25mm] plugs.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

829CK-3/4 Brass Communication Cover Plate

2 5/8" and 3/4" [67mm and 19.1mm] plugs.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

829CK-1/2 Brass Communication Cover Plate

2 5/8" and 1/2" [67mm and 12.7mm] plugs.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

828MAAP A/V Adapter Plate

Sheet metal adapter plate that accepts two (2) Wiremold AVIP or Extron® Electronics MAAP style device plates, sold separately. For use with 828GFITC or 828GFITCAL cover plates, sold separately.

NOTE: UL Listed for terrazzo, polished concrete, wood, tile and carpet covered concrete floors.

Brass covers and flanges are not interchangeable with aluminum or nonmetallic covers and flanges. Nonmetallic covers are interchangeable with aluminum flanges.

FLOOR BOXES

412

FIRE CLASSIFIED FLOOR BOXES
880MP Series Floor Boxes

880MP Series Floor Boxes Metal Cover Plates Ordering Information

828R Brass Duplex Cover Plate

Flip lids. Can also be used with a 106 type communication adapter.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

828GFITC Brass GFI Cover Plate

May be used with Activate and Ortronics® Connectivity Systems in conjunction with 817B, 827B and 837B Flanges.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

828DPGFITC Brass Rectangular Cover Plate

Allows for mounting of a duplex-style receptacle with a rectangular-style flip lid cover.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

### 828DLR Brass Single Locking Receptacle Cover Plate

Single flip lid cover for 20A or 30A single locking receptacles. Device opening is 2 5/8" [67mm]. For use with maximum female locking device of 1.58" diameter and maximum male plug face of 2.25" diameter.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

828SPTC Brass Duplex Cover Plate

Screw plugs. Screw plugs are 1 1/2" [38mm] in diameter.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

829STC Brass Communication Cover Plate

Data slides. Feed through only, not for use with a mounting plate for communication jacks.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

829CK Brass Communication Cover Plate

2 5/8" and 2 1/4" [67mm and 57mm] plugs.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

829CK-1 Brass Communications Cover Plate

2 5/8" and 1" [67mm and 25mm] plugs.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

829CK-3/4 Brass Communications Cover Plate

2 5/8" and 3/4" [67mm and 19.1mm] plugs.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

829CK-1/2 Brass Communications Cover Plate

2 5/8" and 1/2" [67mm and 12.7mm] plugs.

3 1/8" [80.2mm]   4 3/16" [106.2mm]

828MAAP AV Adapter Plate

Sheet metal adapter plate that accepts two (2) Wiremold AVIP or Extron® Electronics MAAP style device plates, sold separately. For use with 828GFITC or 828GFITCAL cover plates, sold separately.

NOTE: UL Listed for tile, terrazzo, polished concrete, wood and carpet floors.

Brass covers and flanges are not interchangeable with aluminum or nonmetallic covers and flanges. Nonmetallic covers are interchangeable with aluminum flanges.

FLOOR BOXES

423

MODULINK™ 880MP SERIES FLOOR BOXES

Modulink 880MP Series Floor Boxes Solid Brass Cover Plate Flanges Ordering Information

817B One-Gang Brass Combination Carpet and Tile Flange

6.080" [154.4mm]   5.060" [128.5mm]

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

837B Three-Gang Brass Combination Carpet and Tile Flange

6.080" [154.4mm]   5.060" [128.5mm]

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

827B Two-Gang Brass Combination Carpet and Tile Flange

6.080" [154.4mm]   5.060" [128.5mm]

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

Modulink 880MP Series Floor Boxes Metal Cover Plates Ordering Information

828R Brass Duplex Cover Plate

3 1/8" [80.2mm]   4 3/16" [106.2mm]

Flip lids. Can also be used with a 106 type communication adapter.

828DLR
Brass Single Locking Receptacle Cover Plate

4 1/8" [105mm]   3 1/8" [79mm]

Single flip lid cover for 20A or 30A single locking receptacles. Device opening is 2 5/8" [67mm]. For use with maximum female locking device of 1.58" diameter and maximum male plug face of 2.25" diameter.

828GFITC Brass GFI Cover Plate

3 1/8" [80.2mm]   4 3/16" [106.2mm]

May be used with Activate and Ortronics® Connectivity Systems in conjunction with 817B, 827B and 837B Flanges.

828SPTC Brass Duplex Cover Plate

3 1/8" [79mm]   4 1/8" [105mm]

Screw plugs are 1 1/2" [38mm] in diameter.

828DPGFITC Brass Rectangular Cover Plate

3 1/8" [80.2mm]   4 3/16" [106.2mm]

Allows for mounting of a duplex style receptacle with a rectangular style flip lid cover.

829STC Brass Communications Cover Plate

3 1/8" [79mm]   4 1/8" [105mm]

Brass communications cover plate, data slides. Feed through only, not for use with a mounting plate for flush mounted communication adapter.

NOTE: Brass covers and flanges are not interchangeable with aluminum or nonmetallic covers and flanges. Nonmetallic covers are interchangeable with aluminum flanges.

OMNIBOX™ SERIES FLOOR BOXES

Omnibox Series Solid Brass Floor Boxes Cover Plate Flanges Ordering Information

817B One-Gang Brass Combination Carpet and Tile Flange

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

6 1/16"
[154.4mm]

5 1/16"
[128.5mm]

827B Two-Gang Brass Combination Carpet and Tile Flange

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

6 1/16"
[154.4mm]

9 1/16"
[230.2mm]

837B Three-Gang Brass Combination Carpet and Tile Flange

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

13 5/16"
[338mm]

6 1/16"
[154.4mm]

817C One-Gang Brass Carpet Flange

For use on 880S1, 880M1, 880CS1-1 and 880CM1-1 Floor Boxes.

5 3/4"
[146mm]

4 3/4"
[121mm]

827C Two-Gang Brass Carpet Flange

For use on 880S2, 880M2, 880CS2-1 and 880CM2-1 Floor Boxes.

5 3/4"
[146mm]

8 7/8"
[225mm]

837C Three-Gang Brass Carpet Flange

For use on 880S3, 880M3, 880CS32-1 and 880CM3-1 Floor Boxes.

5 3/4"
[146mm]

13"
[330mm]

817T One-Gang Brass Tile Flange

For use on 880S1, 880M1, 880CS1-1 and 880CM1-1 Floor Boxes.

4 1/2"
[107mm]

3 1/2"
[88.4mm]

827T Two-Gang Brass Tile Flange

For use on 880S2, 880M2, 880CS2-1 and 880CM2-1 Floor Boxes.

4 1/2"
[114.9mm]

7 5/8"
[193.7mm]

837T Three-Gang Brass Tile Flange

For use on 880S3, 880M3, 880CS3-1 and 880CM3-1 Floor Boxes.

4 1/2"
[114mm]

11 3/4"
[298mm]

Omnibox Series Metal Cover Plates Ordering Information

828R Brass Duplex Cover Plate

Flip lids. Can also be used with a 106 type communication adapter.

3 1/8"
[80.2mm]

4 3/16"
[106.2mm]

828GFITC Brass GFI Cover Plate

May be used with Activate and Ortronics® Connectivity Systems in conjunction with 817B, 827B and 837B Flanges.

3 1/8"
[80.2mm]

4 3/16"
[106.2mm]

**NOTE:** UL Listed for tile, terrazzo and carpet floors.

Brass covers and flanges are not interchangeable with aluminum or nonmetallic covers and flanges.
Nonmetallic covers are interchangeable with aluminum flanges.

FLOOR BOXES

474

Legrand

880W SERIES™ FLOOR BOXES

880W Series Floor Boxes Solid Brass Cover Plate Flanges Ordering Information

### 817B One-Gang Brass Combination Carpet and Tile Flange

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

6 1/16" [154.4mm] 5 1/16" [128.5mm]

827B Two-Gang Brass Combination Carpet and Tile Flange

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

6 1/16" [154.4mm] 9 1/16" [228.6mm]

837B Three-Gang Brass Combination Carpet and Tile Flange

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

6 1/16" [154.4mm] 13 1/16" [338mm]

817C One-Gang Brass Carpet Flange

For use on 880S1, 880M1, 880CS1-1 and 880CM1-1 Floor Boxes.

5 3/4" [146mm] 4 3/4" [121mm]

827C Two-Gang Brass Carpet Flange

For use on 880S2, 880M2, 880CS2-1 and 880CM2-1 Floor Boxes.

5 3/4" [146mm] 8 7/8" [225mm]

837C Three-Gang Brass Carpet Flange

For use on 880S3, 880M3, 880CS32-1 and 880CM3-1 Floor Boxes.

5 3/4" [146mm] 13" [330mm]

817T One-Gang Brass Tile Flange

For use on 880S1, 880M1, 880CS1-1 and 880CM1-1 Floor Boxes.

4 1/2" [107mm] 3 1/2" [88.4mm]

827T Two-Gang Brass Tile Flange

For use on 880S2, 880M2, 880CS2-1 and 880CM2-1 Floor Boxes.

4 1/2" [114.9mm] 7 5/8" [193.7mm]

837T Three-Gang Brass Tile Flange

For use on 880S3, 880M3, 880CS3-1 and 880CM3-1 Floor Boxes.

4 1/2" [114mm] 11 3/4" [298mm]

880W Series Floor Boxes Metal Cover Plates Ordering Information

828R Brass Duplex Cover Plate

Flip lids. Can also be used with a 106 type communication adapter.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

828GFITC Brass GFI Cover Plate

May be used with Activate and Ortronics® Connectivity Systems in conjunction with 817B, 827B and 837B Flanges.

3 1/8" [80.2mm] 4 3/16" [106.2mm]

NOTE: UL Listed for tile, terrazzo and carpet floors.Brass covers and flanges are not interchangeable with aluminum or nonmetallic covers and flanges. Nonmetallic covers are interchangeable with aluminum flanges.

FLOOR BOXES

489

WALKERDUCT® PRO SERIES SERVICE FITTINGS

Walkerduct® Pro Series Service Fittings offer a complete range of service fittings to meet all power and communication requirements while providing flush flanges with interchangeable covers offering an aesthetic appearance.

CODE REFERENCE

cULus Listed Underfloor Raceway Fittings:
File E11912, Guide RQKX

cULus Listed Metallic Outlet Boxes:
File E2961, Guide QCIT

Meets Articles 390 of NEC

Walkerduct Pro Series Solid Brass Cover Plate Flanges & Metal Cover Plates Ordering Information*

817B One-Gang Brass Carpet & Tile Flange

6.080" [154.4 mm]
5.060" [128.5 mm]

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

827B Two-Gang Brass Carpet & Tile Flange

6.080" [154.4mm]
5.060" [128.5mm]

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

837B Three-Gang Brass Carpet & Tile Flange

6.080" [154.4mm]
5.060" [128.5mm]

Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

828R Brass Duplex Cover Plate

3.156" [80.2mm]
4.182" [106.2mm]

Flip lids. Can also be used with a 106 type frame for communication adapter.

828GFITC Brass GFI Cover Plate

3.156" [80.2mm]
4.182" [106.2mm]

May be used with Wiremold CM Series inserts and Ortronics® Connectivity Systems in conjunction with 817B, 827B, and 837B Flanges.

Brass Rectangular Cover Plate

PART NUMBERS:
828DPGFITC (Brass)
828DPGFITCAL (Aluminum)

3.156" [80.2mm]
4.182" [106.2mm]

Allows for mounting of a duplex style receptacle with a rectangular style flip lid cover plate.

*Walkerduct Pro Series Activations are not recommended for concrete floor types. Please consult the factory for concrete applications.

COLOR OPTIONS

Walkerduct® Pro Series Service Fittings are available in brushed aluminum, brass, black or brown as indicated in the part number description.