# MODULINK™ 880MP SERIES FLOOR BOXES




 $Modulink^{\text{TM}}\ Nonmetallic\ Floor\ Boxes\ provide\ power\ and\ communication\ services\ directly\ to\ the\ workstation\ or\ to\ any\ open\ space\ location.$ 

### **CODE REFERENCE**

cULus Listed Nonmetallic Outlet Boxes: File E110748 Guide QCMZ.

## Modulink 880MP Series Floor Boxes Ordering Information

#### 880MP Nonmetallic Rectangular Floor Box




Box comes complete with reusable mudcap, insert spacer, conduit plugs and reducers. Reducers provided for reduction to 1 1/2", 1 1/4", 1", 3/4" and 1/2" [25mm, 19.1mm and 12.7mm] conduit. Minimum concrete depth is 4" [102mm] and maximum concrete depth is 6" [152mm]. Minimum capacity is 50 cu. in. [819mt] and maximum capacity is 100 cu. in. [1693mt]. Box dimensions are 4 1/8" W x 5 1/2" L x 6" H [105mm W x 140mm L x 152mm H].

## 880MPA Nonmetallic Rectangular Floor Box Adjusting Ring



NOTE: One 880MPA is needed for each 880MP and 880MP2 box used. For example, a three-gang box will require three 880MPA Adjusting Rings, ordered separately. Comes with fiber storage loop. Also includes brass inserts for flange connection and green ground wire for ground connection. Wiremold CM Series Open System adapters that snap directly into the adjusting ring without the need for an adapter. Also includes mounting screws to attach flange to box body.

## 880MP2 Nonmetallic Rectangular Floor Box



Box comes complete with reusable mudcap, insert spacer, conduit plugs and reducers. Reducers provided for reduction to 1 1/2", 1 1/4", 1", 3/4" and 1/2" [38mm, 32mm, 25mm, 19.1mm and 12.7mm] conduit. Minimum concrete depth is 4" [102mm] and maximum concrete depth is 6" [152mm]. Minimum capacity is 50 cu. in. [819mt] and maximum capacity is 100 cu. in. [1639mt]. Box dimensions are 4 1/8" W x 8 1/4" L x 6 3/16" [105mm x 210mm x 157mm].

NOTE: Insert spacer should not be removed until after concrete pour.

Box can be connected together to create a two- or three-gang option.

## **COLOR OPTIONS**















Custom color options are also available. Consult the factory for more information.